

Star-Flash LED 627

- Synchronization by infrared diodes in each lamp
- Lamp chain of any length and any number of lamps possible
- Energy-efficient design with only one LED
- Automatic switchover due to discharged rechargeable battery
- High stability by four swivel-out support feet



Light colour
amber



Eff. light intensity day / night
500 cd / 250 cd



Blink-/flash rate
60 fl./min.



Light source
1 resp. 2 LED



Dimensions (LxWxH)
370 x 205 x 95 mm



Weight
ca. 1.6 kg

Star-Flash LED 627

Ref. No.

Star-Flash LED Type 627 A guide light lamp, one-sided amber (According to German Standards) with integrated lithium-ferro battery pack	129091-001-01
Star-Flash LED Type 627 A guide light lamp, two-sided amber, with integrated lithium-ferro battery pack	129091-001-02
Star-Flash LED Type 627 A guide light lamp, one-sided blue (According to German Standards) with integrated lithium-ferro battery pack	129091-001-03
Star-Flash LED Type 627 B guide light lamp, one-sided amber (According to German Standards), for battery operation , without battery	129091-011-01
Star-Flash LED Type 627 B guide light lamp, two-sided amber for battery operation , without battery	129091-011-02

Accessories and Spare parts

Ref. No.

Transport cradle 12/24 V for Star-Flash LED Type 620/627, single, without supply cable	129090-001-00
Transport and charging cradle 12/24 V for Star-Flash LED Type 620/627, single, with 2 m supply cable and 2-pole vehicle plug	129090-001-01
Transport and charging cradle 12/24 V for Star-Flash LED Type 620/627, 4-fold, with 2 m supply cable and 2-pole vehicle plug	129090-004-01
Lithium-Ferro rechargeable battery pack 6,5 V, 1500 mAh for Star Flash 620A/627A	056056-2
AC/DC converter 110-240V, 12V, 5A, for indoor use only, with cigarette lighter socket (for Star-Flash LED 620/627 A)	070098-1
Adapter for using the Nitra, Euro-Nitra, Star-Flash and City Flash on traffic cones	081736-1



In transport and charging cradle



Guide light



with blue lens



Adapter for traffic cones

Operating time with one battery set

With integrated Lithium-Ferro rechargeable battery pack	40 hrs
With battery Premium 800	180 hrs



More information
NIS-01110
To be entered on nissen-germany.com

Test number
V4-25-2012